

Safety Data Sheet

Printing date 03/14/2019

Revised On 03/14/2019

1 Identification of the substance and manufacturer

Trade name: ORIGINAL BLACK
Product code: A-4311-OB
Recommended use: Paint and coating applications.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Press. Gas H280 Contains gas under pressure; may explode if heated.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Repr. 1B H360 May damage fertility or the unborn child.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS04 GHS07 GHS08

Signal word

Danger

Hazard statements

Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 May damage fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	26.12%
74-98-6	propane	15.82%
64742-89-8	VM&P Naphtha	14.57%
106-97-8	n-butane	9.29%
64742-47-8	Mineral Spirits	7.27%
1317-65-3	Calcium Carbonate	4.94%
108-88-3	Toluene	2.61%
67-63-0	Isopropyl Alcohol	2.41%
1333-86-4	Carbon black	1.48%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. on page 2)

Safety Data Sheet

Printing date 03/14/2019

Revised On 03/14/2019

Trade name: ORIGINAL BLACK

(Contd. of page 1)

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
-----------	--

REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
-----------	--

TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm
-----------	--

	Long-term value: 594 mg/m ³ , 250 ppm
--	--

	BEI
--	-----

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
-----------	--

REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
-----------	--

TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX
-----------	--

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
-----------	---

TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)
-----------	--

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift

REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm
-----------	---

	Long-term value: 375 mg/m ³ , 100 ppm
--	--

TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm
-----------	--

	BEI
--	-----

67-63-0 Isopropyl Alcohol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
-----------	--

REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm
-----------	--

	Long-term value: 980 mg/m ³ , 400 ppm
--	--

TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm
-----------	---

	Long-term value: 492 mg/m ³ , 200 ppm
--	--

	BEI
--	-----

1333-86-4 Carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
-----------	--

REL (USA)	Long-term value: 3.5* mg/m ³
-----------	---

	*0.1 in presence of PAHs; See Pocket Guide Apps.A+C
--	---

TLV (USA)	Long-term value: 3* mg/m ³
-----------	---------------------------------------

	*inhalable fraction
--	---------------------

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	50 mg/L
-----------	---------

	Medium: urine
--	---------------

	Time: end of shift
--	--------------------

	Parameter: Acetone (nonspecific)
--	----------------------------------

67-63-0 Isopropyl Alcohol

BEI (USA)	40 mg/L
-----------	---------

	Medium: urine
--	---------------

	Time: end of shift at end of workweek
--	---------------------------------------

	Parameter: Acetone (background, nonspecific)
--	--

Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

(Contd. on page 3)

Safety Data Sheet

Printing date 03/14/2019

Revised On 03/14/2019

Trade name: ORIGINAL BLACK

Eye protection: Tightly sealed goggles

(Contd. of page 2)

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: Not applicable, as aerosol.
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Highly flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: Not determined.
Upper Explosion Limit: Not determined.
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density: Not determined.
Evaporation rate: Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.
VOC content (less exempt solvents): 51.2 %
Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

1333-86-4 Carbon black

Oral LD50 10,000 mg/kg (rat)

Information on toxicological effects: No data available.
Skin effects: Irritant to skin and mucous membranes.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	N/A

(Contd. on page 4)

Safety Data Sheet

Printing date 03/14/2019

Revised On 03/14/2019

Trade name: ORIGINAL BLACK

DOT Consumer Commodity ORM-D
 ADR Aerosols, flammable
 Transport hazard class(es): 1950 AEROSOLS
 Class 2.1
 Special precautions for user: Warning: Gases
 EMS Number: F-D,S-U
 Packaging Group: --
 UN "Model Regulation": UN 1950 AEROSOLS, 2.1

(Contd. of page 3)

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 Isopropyl Alcohol

Toxic Substances Control Act (TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety

Commission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1 Acetone

16 Other information

Contact: Regulatory Affairs