

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57907
 PART NUMBER: C-206
 PRODUCT NAME: FINISH PROTECTOR REMOVER (REVISED 8/06/07)
 CHEMICAL:

SECTION I

| | | |
|--|------------------------|--------------|
| MANUFACTURER: BAF INDUSTRIES | HMIS RATING: | NFPA RATING: |
| ADDRESS: 8010 DIXIE HWY. FLORENCE, KY 41042 | HEALTH: 2 | |
| EMERGENCY TELEPHONE NUMBER: (800) 424-9300 | FIRE: 1 | HEALTH: 2 |
| INFORMATION TELEPHONE NUMBER: (714) 372-5900 | REACTIVITY: 0 | FIRE: 1 |
| DATE PREPARED: 12/16/04 (REVISED 02/18/05) | PERSONAL PROTECTION: B | 0 |
| | | SPEC.HAZ. 0 |
| | | REACT. 0 |

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

| CAS NUMBER | HAZARDOUS COMPONENT | NTP IARC SUB-PART/Z | SARA 313 | OSHA PEL | ACGIH TLV | OTHER LIMITS RECOMMENDED | % |
|-------------------|---------------------|---------------------|----------|----------|-----------|--------------------------|------|
| 111-76-2 | GLYCOL ETHER* | | Y | 25ppm | 25ppm | | 5-10 |
| 6834-92-0 | SODIUM SILICATE | | | N/EST. | N/EST. | | 1-5 |
| (SEE SECTION IX)* | | | | | | | |

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

| | | | |
|-------------------------|------------------------------|---------------------------------------|--------|
| BOILING POINT | 212° F | SPECIFIC GRAVITY (H ₂ O=1) | 1.0115 |
| VAPOR PRESSURE (mm Hg.) | N/AV | MELTING POINT | N/AP |
| VAPOR DENSITY (AIR = 1) | >1 | EVAPORATION RATE (Butyl Acetate = 1) | N/AV |
| SOLUBILITY IN WATER: | COMPLETE | | |
| APPEARANCE AND ODOR: | CLEAR LIQUID WITH MILD ODOR. | | |
| OTHER INFORMATION: | ph =12.67 | | |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| | | | |
|---|-------------------|-----------|-----------|
| FLASH POINT: NON-FLAMMABLE | FLAMMABLE LIMITS: | LEL: N/AV | UEL: N/AV |
| EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER. | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS. | | | |
| UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE. | | | |

SECTION V - REACTIVITY DATA

| |
|--|
| STABILITY: STABLE |
| INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS. |
| HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES. |
| HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. |

SECTION VI - HEALTH HAZARD DATA

| |
|---|
| ROUTE(S) OF ENTRY: SKIN ,EYES |
| HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING - AND BURNING OF EYES AND SKIN. |
| SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE. |
| MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN. |
| EMERGENCY AND FIRST AID PROCEDURES: FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION. |
| OTHER HEALTH WARNINGS: NONE |

MSDS NUMBER: 57907
 PRODUCT NAME: C-206 FINISH PROTECTOR REMOVER. (REVISED 8/06/07)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL..

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED.

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES AND CHEMICAL SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: *CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE 111 OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR, PART 372.

GLYCOL ETHER CAS# 111-76-2 5-10%

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = CORROSIVE LIQUID, N.O.S.
 (CONTAINS SODIUM SILICATE)

PACKING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-----------------|----------------|
| 1. | WATER | CAS# 7732-18-5 |
| 2. | GLYCOL ETHER | CAS# 111-76-2 |
| 3. | SODIUM SILICATE | CAS# 6834-92-0 |

V. O. C. CONTENT: 76 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.
