

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57551
 PART NUMBER: C-61
 PRODUCT NAME: PRO-SOL ADHESIVE LABEL & SILICONE REMOVER (REVISED5/06/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 2 FIRE: 3 REACTIVITY: 0	
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	PERSONAL PROTECTION: B	SPEC.HAZ. 0 REACT.
INFORMATION TELEPHONE NUMBER: (859) 372-5900		
DATE PREPARED: 05/14/03		

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
64742-89-8	NAPHTHA PETROLEUM					100ppm	100ppm		60-100
8052-41-3	PETROLEUM DISTILLATES					100ppm	100ppm		6-9
64742-95-6	AROMATIC HYDROCARBON					N/EST	N/EST		1-5
67-63-0	ISOPROPYL ALCOHOL					400ppm	400ppm		3-7
111-76-2	GLYCOL ETHER **			Y		25ppm	25ppm		3-7

** (SEE SECTION IX)

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	246° F	SPECIFIC GRAVITY (H2O=1)	0.7487
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	VERY LOW		
APPEARANCE AND ODOR:	CLEAR LIQUID WITH SOLVENT ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 67° F	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: CO 2 OR DRY CHEMICAL.		
SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.		
UNUSUAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES AND INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): EXCESSIVE INHALATION MAY CAUSE DROWSINESS OR NAUSEA. MAY CAUSE SKIN AND EYE IRRITATION.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. WASH OFF SKIN. FOR EYE CONTACT WASH COPIOUSLY WITH WATER AND GET MEDICAL ATTENTION. IN CASE OF INGESTION, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57551
 PRODUCT NAME: C-61 PRO-SOL ADHESIVE LABEL & SILICONE REMOVER (REVISED 5/06/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE AWAY FROM FIRE OR FLAME.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL

PERSONAL PROTECTIVE EQUIPMENT: SOLVENT RESISTANT GLOVES AND SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: ** CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) AND 40 CFR PART 372.

** GLYCOL ETHER CAS# 111-76-2 3-7%

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUID, N.O.S.
 (CONTAINING ALIPHATIC HYDROCARBONS)

PACKING GROUP = 111

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

- | | | |
|----|-----------------------|-----------------|
| 1. | NAPHTHA PETROLEUM | CAS# 64742-89-8 |
| 2. | PETROLEUM DISTILLATES | CAS# 8052-41-3 |
| 3. | AROMATIC HYDROCARBON | CAS# 64742-95-6 |
| 4. | ISOPROPYL ALCOHOL | CAS# 67-63-0 |
| 5. | GLYCOL ETHER | CAS# 111-76-2 |

V. O. C. CONTENT: 749 GRAMS PER LITER

THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL WHICH HAS BEEN IDENTIFIED AS A KNOWN CARCINOGEN AS SET FORTH BY I. A. R. C. OR OTHER REGULATORY AGENCY.