

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57837
 PART NUMBER: P-44-H
 PRODUCT NAME: FAST TRAK LIQUID CARNAUBA WAX (REVISED 5/29/08)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING:	NFPA RATING:								
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042	HEALTH: 1	<table style="margin: auto;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">HEALTH</td> <td style="text-align: center;">FIRE</td> </tr> <tr> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="text-align: center;">SPEC.HAZ.</td> <td style="text-align: center;">REACT.</td> </tr> </table>	1	3	HEALTH	FIRE	0	0	SPEC.HAZ.	REACT.
1	3									
HEALTH	FIRE									
0	0									
SPEC.HAZ.	REACT.									
EMERGENCY TELEPHONE NUMBER: (800) 424-9300	REACTIVITY: 0									
INFORMATION TELEPHONE NUMBER: (859) 372-5900	PERSONAL PROTECTION: B									
DATE PREPARED: 05/02/07										

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
64742-89-8	ALIPHATIC HYDROCARBON				300ppm	300ppm		10-30
64742-47-8	ALIPHATIC HYDROCARBON							
7-13								
66402-68-4	CALCINED KAOLIN				5mg/m3	5mg/m3		5-10
471-34-1	CALCIUM CARBONATE				15mg/m3	15mg/m3	1-5	

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	212° F	SPECIFIC GRAVITY (H2O=1)	0.89280
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	MISCIBLE		
APPEARANCE AND ODOR:	YELLOW EMULSION. SOLVENT ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 50° F	FLAMMABLE LIMITS:	LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA: CO 2 OR DRY CHEMICAL.			
SPECIAL FIRE FIGHTING PROCEDURES: FLAMMABLE LIQUID.			
UNUSUAL FIRE FIGHTING PROCEDURES: NONE			

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO 2.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: EYES, SKIN, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): MAY CAUSE EYE AND SKIN IRRITATION. EXCESSIVE INHALATION MAY CAUSE HEADACHES, DIZZINESS, NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR. FLUSH AFFECTED AREA WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE.

MSDS NUMBER: 57837
 PRODUCT NAME: P-44-H FAST TRAK LIQUID CARNAUBA WAX (REVISED 5/29/08)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: TAKE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING.

OTHER PRECAUTIONS: NONE

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GENERAL

PERSONAL PROTECTIVE EQUIPMENT: SAFETY GLASSES AND RUBBER GLOVES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUID, N.O.S. UN1993
 (CONTAINS ALIPHATIC HYDROCARBON)

PACKING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
 N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

1.	WATER	CAS# 7732-18-5
2.	ALIPHATIC HYDROCARBON	CAS# 64742-89-8
3.	ALIPHATIC HYDROCARBON	CAS# 64742-47-8
4.	CALCINED KAOLIN	CAS# 66402-68-4
5.	DIMETHYLPOLYSILOXANE	CAS# 63148-62-9

V. O. C. CONTENT: 140 GRAMS PER LITER