

BAF Industries

MATERIAL SAFETY DATA SHEET

MSDS NUMBER: 57866
 PART NUMBER: S-88
 PRODUCT NAME: VANTAGE NON-SILICONE TIRE DRESSING (REVISED 2/23/10)
 CHEMICAL:

SECTION I

MANUFACTURER: BAF INDUSTRIES	HMIS RATING: HEALTH: 1 FIRE: 3 REACTIVITY: 0 PERSONAL PROTECTION: B	NFPA RATING:
ADDRESS: 8010 DIXIE HWY FLORENCE, KY 41042		
EMERGENCY TELEPHONE NUMBER: (800) 424-9300		
INFORMATION TELEPHONE NUMBER: (859) 372-5900		
DATE PREPARED: 02/11/03		

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS NUMBER	HAZARDOUS COMPONENT	NTP	IARC	SUB-PART/Z	SARA 313	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
142-82-5	ALIPHATIC HYDROCARBON	N	N			400ppm	1640/mg/m3		40-60
64742-89-8	ALIPHATIC HYDROCARBON	N	N			300ppm	300ppm		10-20

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	150° F	SPECIFIC GRAVITY (H2O=1)	0.7512
VAPOR PRESSURE (mm Hg.)	N/AV	MELTING POINT	N/AP
VAPOR DENSITY (AIR = 1)	N/AV	EVAPORATION RATE (Butyl Acetate = 1)	N/AV
SOLUBILITY IN WATER:	NONE		
APPEARANCE AND ODOR:	CLEAR LIQUID. FRUITY ODOR.		
OTHER INFORMATION:	NONE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 15° F TCC	FLAMMABLE LIMITS: LEL: N/AV	UEL: N/AV
EXTINGUISHING MEDIA : FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER.		
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS.		
UNUSUAL FIRE FIGHTING PROCEDURES: TOXIC FUMES MAY BE EMITTED IF MATERIAL IS EXPOSED TO EXTREME TEMPERATURE.		

SECTION V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) : VERY STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND OTHER TOXIC FUMES.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: SKIN, EYES, INHALATION.
HEALTH HAZARDS (ACUTE AND CHRONIC): REDDENING AND BURNING OF EYES AND SKIN, EXCESSIVE INHALATION MAY CAUSE DIZZINESS OR NAUSEA.
SIGNS AND SYMPTOMS OF EXPOSURE: SEE ABOVE.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.
EMERGENCY AND FIRST AID PROCEDURES: REMOVE TO FRESH AIR, FLUSH AFFECTED AREA WITH PLENTY OF WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION.
OTHER HEALTH WARNINGS: NONE

MSDS NUMBER: 57866
PRODUCT NAME: S-88 VANTAGE NON-SILICONE DRESSING (REVISED 2/23/10)

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WIPE UP WITH A NEUTRAL ABSORBANT AND DRUM FOR PROPER DISPOSAL..

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID FREEZING..

OTHER PRECAUTIONS: FLAMMABLE LIQUID AND VAPOR.

SECTION VIII - CONTROL MEASURES

VENTILATION REQUIREMENTS: GOOD VENTILATION SHOULD BE MAINTAINED..

PERSONAL PROTECTIVE EQUIPMENT: RUBBER GLOVES AND SAFETY GLASSES.

SECTION IX - ADDITIONAL INFORMATION

ADDITIONAL MANUFACTURER WARNINGS: NONE.

OTHER PRECAUTIONS AND COMMENTS: D.O.T. PROPER SHIPPING NAME = FLAMMABLE LIQUID, N.O.S
(CONTAINS ALIPHATIC HYDROCARBONS)
UN-1993

PACKING GROUP = II

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BAF INDUSTRIES ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF MATERIAL.

N/AV = NOT AVAILABLE
N/AP = NOT APPLICABLE

THIS INFORMATION IS PROVIDED TO MEET VARIOUS STATE REGULATORY COMPOSITION REQUIREMENTS:

1. ALIPHATIC HYDROCARBON CAS# 142-82-5
2. ALIPHATIC HYDROCARBON CAS# 64742-89-8
3. PROPRIETARY OIL MIXTURE
4. PERFUME MIXTURE

V. O. C. CONTENT: 520 GRAMS PER LITER