



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT

Bulletin



- **Semi-Gloss Enamel Paint**
- **Renews Factory Black Appearance**
- **Concentrated 5-to-1 For Economy**
- **Fast Drying Formula**

- **Heat Resistant**
- **Apply With Conventional Spray Equipment**
- **For Engines, Fender Wells & More**
- **Will Not Crack, Chip or Peel**

4511

BLACK ENAMEL ENGINE PAINT

CONCENTRATE

FEATURES AND BENEFITS

Burford's® BLACK ENAMEL ENGINE PAINT is a high quality, concentrated (5:1) engine enamel that restores the factory, semi-gloss look to all areas of the engine compartment, safely and quickly. The fast-drying, heat resistant formula provides excellent coverage and adhesion to all pre-cleaned metal and rubber surfaces. Renews the appearance of engine compartments, hoses, belts, cables, wires, distributors, radiators, fire walls, tires, fender wells, tools, equipment, machinery, rubber floor mats and more. Will not crack, chip or peel. Burford's® 4511 is designed for economy. This innovative concentrate can be mixed with three types of thinning agents: lacquer thinner, paint thinner or gasoline. Mix one part 4511 concentrate with up to five gallons of lacquer thinner, gasoline or paint thinner to produce a very cost effective black enamel paint. Apply with pistol sprayer, pressure pot (Sure Shot™) or any conventional spray equipment.

RECOMMENDED FOR

Burford's® 4511 is a rich, durable black paint that covers well and restores the appearance of engine compartments, hoses, belts, cables, wires, distributors, radiators, fire walls, tires, fender wells, tools, equipment, machinery, rubber floor mats and more. 4511 is safe and effective on all pre-cleaned metal and rubber surfaces.

APPLICATION

Directions: Shake well before using. For your protection, safety glasses and rubber gloves are recommended while using this product. Keep container closed when not in use. For best results, area to be coated should be clean and free of dirt & grease. Pre-clean engine compartment with PRO® C-51 Red Devil™ Engine Degreaser. Allow to dry completely. Smooth rust and rough areas with wire brush or steel wool. Mix one (1) part 4511 Black Engine Compartment Paint with up to five

(5) parts lacquer thinner, paint thinner or gasoline for normal conditions. Hard to cover areas may require a stronger concentration of paint. NOTE: FLAMMABLE LIQUID-DO NOT APPLY ONTO HOT SURFACE. Apply with pistol sprayer, pressure pot (Sure Shot™) or any conventional spray equipment (35-40 psi air pressure). Apply in even thin coats rather than one heavy application. Spray diluted product onto clean, dry surface and allow to dry for approximately 10 minutes. Repeat as necessary.

SPECIAL NOTES

Hard to cover areas may require a stronger concentration of paint. In such a case, use less thinner.

PACKAGING

GALLON/4 PER CASE
5 GALLON PAIL