



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!  
Since 1935

# PRODUCT

## Bulletin



- **Ready to Use**
- **Invisible Polymer Coating**
- **Repels Stains, Dirt and Wetness**
- **Clear in Color-Leaves no Residue**
- **Non Chlorinated Solvent**
- **Eliminates Static Buildup**
- **Allow 3 to 4 Hours Curing Time**

## APG-88

# PRO®-GARD™

# Aerosol Fabric Protector

### FEATURES AND BENEFITS

APG-88 AEROSOL PRO®-GARD™ is an aerosol version of our popular polymer based fabric protector. A coating that repels stains, soils, grime and eliminates static buildup on carpets, upholstery and fabrics. PRO®-Gard™ is a special blend of polymers that surrounds each individual fiber of the material with an invisible shield and protects against oil, dirt, grime and stains. Protects against spills from products such as coffee, soda, milk or similar liquids or solids. Its fast drying, non-chlorinated solvent is safe for all automotive fabrics and protects the surface without affecting the texture or flexibility of the fabric. Even when spills penetrate loose weave fabric, they are easily blotted up clean, since each fiber has already been treated.

### RECOMMENDED FOR

APG-88 is designed for use on all natural and synthetic fabrics to help repel water, oil, dirt, grime and stains. PRO®-Gard™ is excellent for use on all fabrics and velour seats, carpets, trunks and upholstery. Use around the auto, home, office or anywhere a fabric protector is desired.

### APPLICATION

**Shake well before using.** On dirty surfaces, clean area with PRO® AHF-400 Fabric Cleaner, ASF-450 Super Foam Fabric Cleaner, C-49 HD Interior Cleaner or C-54 Upholstery & Carpet Cleaner prior to application of PRO®-Gard™. For best results, use when can is between 70° and 90°F (21° and 32°C). Point opening of spray button toward object to be treated, holding can 8 to 12 inches (20 to

30 cm) from surface. Press spray button firmly and spray liberally using a sweeping motion. Apply in criss-cross pattern to insure complete wetting. Allow 3 to 5 hours drying time before using vehicle. Curing is recommended before customer delivery. Repeat steps if necessary. If clogging develops, turn spray button 1/4 turn. If clogging persists, remove and clean spray button with a twisting motion, holding top of can and spray button opening pointed away from you.

### SPECIAL NOTES

Also available in bulk form (PG-77).

### PACKAGING

20 OZ. CAN/12 PER CASE  
QUART/12 PER CASE