



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT

Bulletin

MEMBER



- **10:1 Concentrate**
- **Blended with Three Effective Acids**
- **Cleans Wire Wheels, Chrome & Stainless Steel on Contact**
- **Contains Corrosive Inhibitors**

- **Removes Brake Dust, Rust, Oxidation & Road Grime**
- **Spray On, Hose Off**
- **Leaves No Film or Residue**

C-24

PRO® POWER ACID CLEANER

FEATURES AND BENEFITS

PRO® POWER will make even the worst surfaces sparkle without scrubbing. C-24 is an extremely potent, concentrated (10:1) acid base formula designed for use everyday in detail shops and dealerships everywhere. C-24 is a combination of specially blended acids formulated to deep clean and return natural luster to recommended surfaces. C-24 requires no precleaning of surfaces. Just spray on and hose off. It's as simple as that! PRO® POWER clings to contaminants and penetrates for fast, effective rinsing. Works so quick and clean, it leaves no residue or dulling road film.

C-24 contains special corrosion inhibitors to protect the surface and prolong the shine. Makes light work of heavy deposits.

RECOMMENDED FOR

PRO® POWER was designed for the fast and effective removal of surface rust, brake dust, oxidation, corrosion and road grime on wire wheels, stainless steel, chrome plated finishes and porcelain. C-24 cleans and brightens trailers, trucks, boats, automotive and transportation equipment.

APPLICATION

SHAKE WELL BEFORE USING. Safety goggles, vapor respirator, chemical resistant rubber gloves and synthetic apron must be worn while using this product. Do not apply to a warm surface. Use in well ventilated area. Dilute 1 part C-24 with up to

10 parts water. Dilution ratio depends on surface to be cleaned. Allow product to react on surface for 1 to 2 minutes. Do not allow to dry. Rinse surface thoroughly with water. Wipe dry. For extreme cases, a stronger dilution or light agitation with a soft brush may be necessary.

SPECIAL NOTES

Read MSDS before using. Do not use on porous anodized, magnesium, aluminum or coated wheels. Avoid contact with glass or painted surfaces as frosting or etching may occur.

PACKAGING

GALLON/4 PER CASE
5 GALLON CUBE
55 GALLON DRUM