



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- Formulated Specifically for Black & Other Dark Color Paints
- One Step Cleaner Polish & Wax
- Removes Swirl Marks, Cobweb Scratches & Paint Finish Roughness

- Blend of Carnauba & Polymers Yield a Deep, Dark Protective Shine
- Hand or Machine Use
- VOC Compliant

P-29 **BLACK BEAUTY™** *Color Brightener & Sealer*

FEATURES AND BENEFITS

P-29 BLACK BEAUTY™ is a professional one-step color brightener and sealer, specially formulated for black and other dark color paints. Quickly and effectively removes fine swirl marks and cobweb scratches, while leaving a swirl-free, deep, dark protective shine. Contains a blend of carnauba wax and polymers for long term, high gloss protection. Clear coat safe. VOC Compliant.

RECOMMENDED FOR

BAF Industries designed P-29 for clearcoat paint finishes. Also, P-29 is recommended for new water base paints and all finishes that do not require a heavy precleaning. P-29 is a fast working cleaner polish designed to remove light surface oxidation and light scratches while polishing to a rich luster. Recommended for hand or machine use.

APPLICATION

SHAKE WELL BEFORE USING. Safety glasses and rubber gloves are recommended while using this product. See MSDS for additional safety information.

Hand Use: Apply product to a clean, cotton wax applicator and spread product evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (approx. 1 minute) and wipe off with a clean, soft, microfiber towel. Polish by hand to a high gloss, turning towel while wiping down.

DA Use: Apply product to applicator and spread evenly over small area of paint surface before buffing. Use a CM-6-F charcoal foam polish pad or WM-6-F white foam finish pad. Set the speed to 5 and work the product over the surface. Continue to polish until product disappears.

High Speed Buffer: NIOSH approved dust mask and safety glasses are recommended while high speed buffing this product. Apply product to applicator and spread evenly over small area of paint surface before buffing. Use a RV-

85-C charcoal foam polish pad or BV-85-C blue foam finish pad. Buff with adequate pressure @ 1500 - 2300 rpm. As product dries, reduce pressure and burnish to a high gloss. Clean pad often to remove contaminants. For added protection, finish with P-35-Q Satin Creme™ Sealer Wax, P-36 Cherry Finishing Wax™ or P-63 Poly Gard™ Paint Sealant.

SPECIAL NOTES

Prior to application, check paint surface. If paint finish roughness detected, use C-105 Clay Away™ first to smooth the surface. Do not apply P-29 in direct sunlight or to a hot surface.

PACKAGING

PINT/12 PER CASE
GALLON/4 PER CASE