



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT *Bulletin*



- **Brilliant Finish - Clearcoat Safe**
- **One Step Cleaner Polish & Wax**
- **Removes Fine Scratches, Buffer Marks & Light Oxidation**

- **Contains Carnauba Wax & Amino functional Silicones**
- **Hand or Machine Use**
- **VOC Compliant**

P-31 #1 POLISH™ Clearcoat Formula

FEATURES AND BENEFITS

P-31 #1 POLISH™ is a professional formulation specifically designed for the basecoat/clearcoat systems. It removes light oxidation, minor scratches and swirl marks. P-31 is made with very mild abrasives which clean and polish the surface in a one-step operation. P-31 will not scratch the clearcoat layer of today's new two-stage paint systems. The end result with P-31 is a deep, swirl-free, glass like finish.

RECOMMENDED FOR

BAF Industries designed P-31 with the new basecoat/clearcoat system finishes in mind. Also, P-31 is recommended for new water base paints and all finishes

that do not require a heavy precleaning. P-31 is a fast working cleaner polish designed to remove light surface oxidation and light scratches while polishing to a rich luster. Recommended for hand or machine use.

APPLICATION

SHAKE WELL BEFORE USING. For hand application, apply P-31 with a dispenser bottle to a clean cloth and rub into finish well. Let dry to haze and wipe, using a PT-8 micro fiber towel, to a high luster. For orbital polisher application, apply P-31 to bonnet, turn on buffer and spread product over the finish. When finish is dry, buff to a high luster with a clean bonnet. For high speed application, apply a small amount of P-31 from a dispenser bottle to

the painted surface. Before turning on the high speed buffer spread the product over a small area with the buffing pad. Using a VF-85-C foam pad, work small sections. Buff while wet to a high luster.

SPECIAL NOTES

Prior to application, check paint surface. If it feels rough, use P-40 Duz All® first to smooth the surface. Do not apply P-31 in direct sunlight or to a hot surface.

PACKAGING

PINT/12 PER CASE
GALLON/4 PER CASE