



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!  
Since 1935

# PRODUCT *Bulletin*



- **One Step Polish & Wax**
- **Formulated for Single Stage Paints**
- **Contains Natural Oils, Silicone & Waxes**
- **Machine Use Recommended**

- **Great for Metallics, Blacks & Reds**
- **Revitalizes Faded Finishes by Restoring Lost Oils**
- **VOC Compliant**

## P-33 **TROUBLESHOOTER®** Sealer & Color Brightener

### FEATURES AND BENEFITS

P-33 TROUBLESHOOTER® is a product that has been a staple in the industry for years. TROUBLESHOOTER® is a sealer & color brightener formulated to overcome the problem finishes such as metallics, blacks, reds and blues. Mild cleaners remove compound scratches, swirl marks, light oxidation and cobwebbing. It feeds the paint with the necessary oils to bring back depth and clarity, while carnauba and other waxes and polymers seal in the shine for long lasting beauty. New combinations of Carnauba Wax and lubricating oils allow the user to polish with no worries of bogging down or gumminess, due to climatic conditions. It cuts fast and cleans with ease. P-33 leaves a dry, hard, glass like finish free of buffer or swirl marks.

### RECOMMENDED FOR

P-33 is designed for new car prep, used car reconditioning, removal of light oxidation. Recommended for hand or machine use. It works on single stage or clear coat paint with excellent results.

### APPLICATION

**Directions: Shake well before using.** Safety glasses and NIOSH dust mask are recommended while using this product. For best results, do not apply in direct sunlight or onto a hot surface.

**Hand Use:** Apply product to a clean, cotton wax applicator and spread product evenly over small area of painted surface, rubbing well in a circular motion. Let dry to a haze (approx. 3 minutes) and wipe off with a PRO® PT-8 Microfiber Polishing

Cloth. Polish by hand to a high gloss, turning cloth while wiping down.

**Orbital Use:** Apply product to a clean bonnet. Turn on orbital and spread product evenly over surface. Let dry to a haze (approx. 3 minutes). Remove with a clean, dry bonnet and burnish to a high gloss finish.

**High Speed Buffer:** Apply product to wax applicator and spread evenly over small area of paint surface before buffing. Use a VC-80-C wool cutting pad or VF-85-C yellow foam polish pad. Buff with adequate pressure @ 1400 - 2300 rpm. As product dries, reduce pressure and burnish to a high gloss. Clean pad often to remove contaminants.

### PACKAGING

1 GALLON/4 PER CASE