



PRO® and Burford's® are registered trademarks of BAF Industries.

The Professional's Choice!
Since 1935

PRODUCT

Bulletin

MEMBER



- **Carnauba Wax & Premium High Grade Polymers Provide Maximum Gloss & Protection**
- **Cleans, Polishes & Protects in One Operation**
- **One Step Cleaner Wax**

- **Durability 60-90 Days**
- **Great on Autos, Campers, RV's, Boats, Airplanes, Plexiglass & Fiberglass**
- **Formulated for Single Stage Paints**
- **VOC Compliant**

P-57

MIRACLE WAX™

CREAM

FEATURES AND BENEFITS

For over 30 years, P-32 MIRACLE WAX™ was the standard by which all cleaner waxes were measured. P-57 MIRACLE WAX™ CREAM has the same high quality ingredients that made MIRACLE WAX™ such a success. This rich, creamy blend of carnauba and other fine imported waxes, coupled with two durable polymer resins, leaves a deep lustrous finish. P-57 offers superior protection from oxidation, sun fading, harsh detergents, salt, tree sap and bird droppings. Just one P-57 application will clean, wax and protect the vehicle with the most remarkable shine.

RECOMMENDED FOR

P-57 is designed to produce a brilliant, long lasting shine on all finishes, including chrome, fiberglass and plastic.

Recommended for the removal of light to medium oxidation, light surface scratches and dulling road film. P-57 is great on all autos, campers, boats, planes and recreational vehicles. Excellent for hand or machine use.

APPLICATION

SHAKE WELL BEFORE USING.

Hand Use : apply P-57 to a clean, soft, dry pad or wax applicator. Wipe product evenly over a small area of painted surface, rubbing well in a circular motion. Let dry to a haze (about 1 minute) and wipe off to a high luster using a PT-8 Microfiber Cloth

Orbital Buffer/DA: Apply P-57 to orbital bonnet. Turn on machine. Buffing with adequate pressure, spread uniformly over a small area of paint surface. Let dry to haze, then change to a clean dry bonnet and remove excess material. Burnish to a high gloss finish.

High Speed Buffer: Use with a 1500-2500rpm buffer. Apply sparingly to buffing pad. Spread uniformly on paint surface before buffing. Buff with adequate pressure. As product dries, reduce pressure and burnish to a high gloss finish using a VC-80-C wool cutting pad for deep cleaning and polishing or a VF-85-C Foam Polishing Pad for light to medium buffing.

SPECIAL NOTES

Extremely oxidized surfaces may require an additional application. For best results, do not apply P-57 in direct sunlight or on extremely hot finishes.

PACKAGING

PINT/12 PER CASE
GALLON/4 PER CASE