



Product Bulletin



SYNERGY CERAMIC DETAIL SPRAY

Product Description:

Synergy Ceramic Detail Spray is a quick detail spray for vehicles that have been treated with Synergy Coatings. The product is designed as an easy-to-use, spray and wipe detail spray booster for coating preservation. Formulated to maintain and enhance the brilliant shine and protection of Synergy Coatings.

Synergy Ceramic Detail Spray is designed to instantly bond to protect, strengthen and enhance the performance of the coating structure. Using Synergy Ceramic Detail Spray on a regular basis will bring new life back as well as extend the life of Synergy Ceramic Coating with a single application.

Synergy Ceramic Detail Spray conditions the vehicle's protective coating by safely and effectively removing light dirt, dust, bird droppings, fingerprints, holograms, water spots and contamination while adding protective polymers back into the coating. Synergy Ceramic Detail Spray adds a high gloss shine to any color paint finish for the highest quality results after each application. Synergy Ceramic Detail Spray uses synthetic protection to create a durable shield with stunning shine and gloss.

Synergy Ceramic Detail Spray restores the surface strong hydrophobic properties. Synergy Ceramic Detail Spray forms a highly durable, long-lasting, impervious protective shield that effectively repels water, dust, dirt, and oils, dissipates static, and adds additional protection to the painted finish. The polymer sealant spray dries clear and instantly leaves each treated surface with enhanced gloss, slickness, and extreme hydrophobicity for up to 3 months after each use. The Synergy Ceramic Detail Spray formula is packed with hydrophobicity and high-quality glossing agents. When sprayed onto a coated surface, the glossing agents fill in imperfections while the hydrophobic formula restores the incredible water beading and sheeting effects of Synergy Ceramic Coating.

Use Synergy Ceramic Detail Spray between washes and after washes to help protect against UV rays, contamination, discoloration, water spots, salt, corrosive chemicals, bugs, bird droppings and much more. Synergy Ceramic Detail Spray is the perfect spray sealant to apply after a weekly wash. Synergy Ceramic Detail Spray keeps paint clean and glossy longer, makes car washing easier and allows it to dry faster. Simply apply after a wash to extend coating protection in all climates and weather conditions.

Synergy Ceramic Detail Spray can be used on all exterior surfaces, including painted finish, glass, plastic trim, moldings, wheels, rubber, aluminum, fiberglass and chrome surfaces. The versatile spray sealant can be applied when the surface is wet or dry making it perfect for topping coated vehicles protection and shine.

Synergy Ceramic Detail Spray can be used as a standalone product or as a booster for Synergy Ceramic Coating. Synergy Ceramic Detail Spray is also compatible with Synergy Trim and Glass Coatings as well as traditional finish waxes and sealants.

Enhance, Extend, Restore and Revitalize...Synergy Ceramic Detail Spray!

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com



Features & Benefits:

- Enhances and Maintains Synergy Coatings
- Extends Coating Life
- Restores Hydrophobicity
- Revitalizes Gloss & Slickness
- Removes Dirt, Dust and Fingerprints
- Provides UV Protection
- Fast and Easy – Spray & Wipe
- Apply to Wet or Dry Surface
- Lasts Up to 3 Months

Directions:

1. Wash vehicle with C-60 Super Car Wash.
2. Shake well before using.

Spraying: Working one panel at a time, apply product directly to the surface with a trigger sprayer. Using a clean, microfiber towel, spread product evenly and wipe surface with light pressure. As product dries, turn cloth and wipe to a high gloss.

Wiping: Working one panel at a time, apply product to a clean microfiber wax applicator and spread evenly over small area of painted surface with light pressure. As product dries, wipe off with a clean, microfiber towel. Turn towel regularly and hand polish to a high gloss, wet look finish.

3. Repeat application for each coated panel.

Notes:

- Use recommended personal protective equipment
- Recommended application temperatures 40° F - 90° F
- Do not apply in direct sunlight or to a hot surface. Apply in a shaded, dust free area
- May be applied after every wash or regularly as needed
- **⚠WARNING:** Reproductive Harm - www.p65Warnings.ca.gov